MOTOREX Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: ANTIRUST SPRAY
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Anticorrosion additive Only for proper handling.

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MOTOREX AG Bern–Zürich–Strasse 31, Postfach CH–4901 Langenthal Tel. +41 (0)62 919 75 75 www.motorex.com

- · Further information obtainable from: msds@motorex.com
- · 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 (UK only).

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if

heated.

Eve Irrit. 2 H319 Causes serious eve irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated

exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02 GHS07 GH

· Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Distillates (petroleum), hydrotreated light paraffinic

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

MOTOREX Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 1) · Precautionary statements P101 If medical advice is needed, have product container or label at hand. Keep out of reach of children. P102 P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. P211 P251 Do not pierce or burn, even after use. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P273 Avoid release to the environment. P280 Wear eye protection / face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

international regulations.

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304, EUH066	10-25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	≥10-<20%
CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3 Reg.nr.: 01-2119487077-29	Distillates (petroleum), hydrotreated light paraffinic Asp. Tox. 1, H304	10-25%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	≥5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2.5-7.5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.5%

(Contd. on page 3)

Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 2)

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons

≥30%

· Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Remove residues with soap and water.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

MOTOREX*
Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 3)

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

- Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

•	8.	1 C	on	tro	l pai	ran	iete	ers
---	----	-----	----	-----	-------	-----	------	-----

Ingredien	ts with limit values that require monitoring at the w	orkplace:				
106-97-8	butane, pure					
Long	/EL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)					
71-36-3 b	utan-1-ol					
WEL Sho	rt-term value: 154 mg/m³, 50 ppm					
DNELs						
Hydrocar	bons, C9-C11, n-alkanes, isoalkanes, cycloalkanes,	<2% aromatics				
Oral	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)				
Dermal	DNEL / Workers / Systemic effects / Long-term	300 mg/kg/24h (worker)				
	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)				
Inhalative	DNEL / Workers / Systemic effects / Long-term	1,500 mg/m3 (worker)				
	DNEL/general population/Systemic effects/Long-term	900 mg/m3 (consumer)				
64742-55-	8 Distillates (petroleum), hydrotreated light paraffii	nic				
Dermal	DNEL / Workers / Local Effects / Long-term	1 mg/kg/8h (worker)				
Inhalative	DNEL	2.7-5.4 mg/m3/8h (worker)				
	DNEL	1.2 mg/m3/24h (consumer)				
Hydrocar	bons, C9-C12, n-alkanes, isoalkanes, cyclics, arom	atics (2-25%)				
Oral	DNEL/general population/Systemic effects/Long-term	26 mg/kg/24h (consumer)				
Dermal	DNEL / Workers / Systemic effects / Long-term	44 mg/kg/24h (worker)				
	DNEL/general population/Systemic effects/Long-term	26 mg/kg/24h (consumer)				
Inhalative	DNEL/general population/Systemic effects/Long-term	71 mg/m3 (consumer)				
71-36-3 b	utan-1-ol					
Oral	DNEL/general population/Systemic effects/Long-term	3.125 mg/kg/24h (consumer)				
Inhalative	DNEL / Workers / Local Effects / Long-term	310 mg/m3 (worker)				
	DNEL/general population/Local effects/Long-term	55 mg/m3 (consumer)				

(Contd. on page 5

MOTOREX*
Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

		(Contd. of page
PNE		light payaffinia
04/4	2-55-8 Distillates (petroleum), hydrotreated	
Oral	PNEC / Predators / Secondary poisoning	9.33 mg/kg food (secondary poisoning (predators))
71-3	6-3 butan-1-ol	
	PNEC / Aquatic organisms / Freshwater	0.082 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Marine water	0.0082 mg/l (aquatic organisms)
	PNEC/Aquatic org/intermittent releases(freshwater)	2.25 mg/l (aquatic organisms)
	PNEC/Aquatic organisms/Sewage treatment plant/STP	2,476 mg/l (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (freshwater)	0.178 mg/kg (aquatic organisms)
	PNEC / Aquatic organisms / Sediment (marine water)	0.0178 mg/kg (aquatic organisms)
	PNEC / Terrestrial organism / Soil	0.015 mg/kg (terrestrial organisms)

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



(Contd. on page 6)



Printing date 21.10.2024 Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 5)

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol · Colour: Black Solvent-like · Odour: Odour threshold: Not determined. Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

0.5 Vol % · Lower: 8.5 Vol % · Upper: <-10 °C · Flash point:

Not determined. · Decomposition temperature: · pH Not determined.

· Viscosity:

< 1 mm²/s @40 °C (DIN 51562-1) · Kinematic viscosity

· Consistency

Not determined. · Dynamic:

Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log

value)

· Heat Capacity

Not determined. · Vapour pressure:

· Density and/or relative density

0.709 g/cm3 (ASTM D 4052) · Density at 20 °C:

Not determined. Relative density Not determined. · Vapour density

· 9.2 Other information

· Appearance:

· Form: Liquefied gas

· Important information on protection of health

and environment, and on safety.

· Explosive properties: Product is not explosive. However, formation of

Not determined.

explosive air/vapour mixtures are possible.

· Solvent separation test:

· VOC (EC) 89.23 %

Change in condition

 Evaporation rate Not applicable.

· Information with regard to physical hazard

classes · Explosives

Void · Flammable gases Void

Extremely flammable aerosol. Pressurised · Aerosols

container: May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void

(Contd. on page 7)

MOTOREX*
Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

		(Contd. of page 6)
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
Organic peroxides	Void	
· Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	LD/LC50 values relevant for classification:			
106-97-8	106-97-8 butane, pure			
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)		
	LC50 / 15 min	800,000 ppm (rat)		
	LC50 / 2h	1,237 mg/l (mouse)		
	LC50 / 2h	520,400-539,600 ppm (mouse)		
	LC50 / 4h	658 mg/l (rat)		
	NOAEC	4,000-16,000 ppm (rat)		
	NOAEC	7.2-21.4 mg/l (rat)		
	LOAEC	21.6 mg/l (rat)		
	LOAEC	12,000 ppm (rat)		
Hydrocar	bons, C9-C11,	n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Oral	LD50	5,000-15,000 mg/kg (rat)		
	NOAEL	1,000-5,000 mg/kg/24h (rat)		
Dermal	LD50	2,000 mg/kg (rat)		
		3,160-5,000 mg/kg (rabbit)		
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)		
	LC50 / 8h	41-4,467 ppm (rat)		
	LC50 / 8h	5 mg/l (rat)		
	NOAEL	200 ppm (rat)		
	NOAEC	275-10,400 mg/m3 (rat)		
	L		(Contd. on page 8)	

— GF



Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

64740 EE	O Distillatos (n	atralaum) budratraatad light navaffinia	(Contd. of pa
		etroleum), hydrotreated light paraffinic	
Oral	LD50	5,000 mg/kg (rat)	
D /	LOAEL	125 mg/kg/24h (rat)	
Dermal	LD50	2,000-5,000 mg/kg (rabbit)	
	NOAEL	150 mg/kg/24h (mouse)	
		30-2,000 mg/kg/24h (rat)	
		1,000 mg/kg/24h (rabbit)	
	LOAEL	100 mg/kg/24h (mouse)	
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)	
	NOEL	220 mg/m3 (rat)	
	NOAEL	980 mg/m3 (rat)	
-		n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Oral	LD50	15,000 mg/kg (rat)	
Dermal	LD50	4 ml/kg (rat)	
	NOAEL	495 mg/kg/24h (rat)	
Inhalative	LC50 / 4h	13.1 mg/l (rat)	
	NOAEL	300 ppm (rat)	
	NOAEC	690 ppm (rat)	
	LOAEC	100-1,293 ppm (rat)	
74-98-6 p	•		
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)	
	LC50 / 15 min	800,000 ppm (rat)	
	LC50 / 2h	1,237 mg/l (mouse)	
	LC50 / 2h	520,400-539,600 ppm (mouse)	
	NOAEC	4,000-16,000 ppm (rat)	
	NOAEC	7.214-21.394 mg/l (rat)	
	LOAEC	21.64 mg/l (rat)	
	LOAEC	12,000 ppm (rat)	
71-36-3 b	utan-1-ol		
Oral	LD50	2,292 mg/kg (rat)	
	LD50	2.83 ml/kg (rat)	
	NOEL	125 mg/kg/24h (rat)	
	LOEL	500 mg/kg/24h (rat)	
Dermal	LD50	4.24 ml/kg (rabbit)	
	LD50	3,430 mg/kg (rabbit)	
Inhalative	LC50 / 4h	17.76 mg/l (rat)	
	NOEL	500 ppm (rat)	

- Primary irritant effect:
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

MOTOREX*
Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 8)

Aquatic	toxicity:
106-97-8	8 butane, pure
LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)
-	arbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
LL50	1,000 mg/l/96h (fish)
LL50	1,000 mg/l/72h (fish)
LL50	1,000 mg/l/48h (fish)
LL50	1,000 mg/l/24h (fish)
LL0	100 mg/l/96h (fish)
EL50	1,000 mg/l/48h (aquatic invertebrates)
EL50	1,000 mg/l/24h (aquatic invertebrates)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
EL0	1,000 mg/l/48h (aquatic invertebrates)
	0.131 mg/l/28d (fish)
	0.23 mg/l/21d (aquatic invertebrates)
	3-100 mg/l/72h (algae / cyanobacteria)
	5-8 Distillates (petroleum), hydrotreated light paraffinic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
	>100 mg/l/96h (Pimephales promelas) (OECD 203)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
NOEL	>100 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201)
	arbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
EC10	0.109-0.248 mg/l/21d (aquatic invertebrates)
EC50	0.58-1.2 mg/l/96h (algae / cyanobacteria)
EC50	0.53-0.94 mg/l/72h (algae / cyanobacteria)
EC50	0.328-0.423 mg/l/21d (aquatic invertebrates)
LL50	10-30 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	10-30 mg/l/48h (fish)
LL50	30-100 mg/l/24h (fish)
EL50	2.5-5.5 mg/l/96h (algae / cyanobacteria)
EL50	10-22 mg/l/48h (aquatic invertebrates)
EL50	22-46 mg/l/24h (aquatic invertebrates)
NOEC	0.097-0.372 mg/l/21d (aquatic invertebrates)
NOEC	0.16 mg/l/72h (algae / cyanobacteria)
NOEC	0.16 mg/l/96h (algae / cyanobacteria)
NOELR	0.13 mg/l/28d (fish)

Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

	(Contd. of page 9)
NOELR	0.3 mg/l/96h (fish)
LOEC	0.203-0.833 mg/kg/28d (aquatic invertebrates)
74-98-6	propane
LC50	24.11-147.54 mg/l/96h (fish)
LC50	14.22-69.43 mg/l/48h (aquatic invertebrates)
EC50	7.71-19.37 mg/l/96h (algae / cyanobacteria)
71-36-3	butan-1-ol
LC50	1,376 mg/l/96h (fish)
EC50	225 mg/l/96h (algae / cyanobacteria)
EC50	18 mg/l/21d (aquatic invertebrates)
EC50	1,328 mg/l/48h (aquatic invertebrates)
NOEC	4.1 mg/l/21d (aquatic invertebrates)
NOEC	519 mg/l/96h (fish)
NOEC	415 mg/l/48h (aquatic invertebrates)
. 12 2 Pai	rsistence and degradability No further relevant information available

· 12.2 Persistence and degradability No lutther relevant information available.				
· 12.3 Bioaccumulat	· 12.3 Bioaccumulative potential			
106-97-8 butane, p	ure			
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)			
Hydrocarbons, C9	-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
Biodegradability	80 % (28d) (Bioaccumulation) (OECD 301 F)			
64742-55-8 Distilla	tes (petroleum), hydrotreated light paraffinic			
Partition coefficient	>3.5 [] (log Kow) (Bioaccumulation)			
Hydrocarbons, C9	-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
Biodegradability	74.7 % (28d) (Biodegradability) (OECD 301 F)			
74-98-6 propane				
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)			
71-36-3 butan-1-ol				
Partition coefficient	1 [] (log Kow) (Bioaccumulation)			
Biodegradability	>70 % (28d) (Biodegradability) (OECD 301 A)			

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

MOTOREX*
Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 10)

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/RID/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/RID/ADN 1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN



· Class 2 5F Gases.

· **Label** 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

14.4 Packing group

· ADR/RID/ADN, IMDG, IATA Not classified as hazardous for transport

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

Hazard identification number (Kemler code): -

· EMS Number: F-D,S-U

· Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

(Contd. on page 12)

GB

MOTOREX*
Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

	(Contd. of page 1
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR/RID/ADN Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
IMDG	41
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 13)

Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 12)

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· purity requirement

Relevant phrases

H220 Extremely flammable gas. H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eve damage. H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

Toxic to aquatic life with long lasting effects. H411

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Abteilung Produktsicherheit

· Abbreviations and acronyms:

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

Annex: Exposure scenario 1

- · Short title of the exposure scenario Industrial use of anticorrosion agents
- Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC14 Metal surface treatment products
- · Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- Physical parameters
- Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.

(Contd. on page 14)

Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 13)

- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 2

- · Short title of the exposure scenario Professional use of anticorrosion agents
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC14 Metal surface treatment products
- · Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging

(Contd. on page 15)

MOTOREX*
Oil of Switzerland
Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 14)

- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 3

- · Short title of the exposure scenario Private use of anticorrosion agents
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Product category PC14 Metal surface treatment products
- · Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.
- Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 4

- · Short title of the exposure scenario Industrial use of sprays
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category
 - PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- Process category PROC11 Non industrial spraying
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

(Contd. on page 16)

Revision: 21.10.2024

Printing date 21.10.2024

Version number 4.0 (replaces version 3.3)

Trade name: ANTIRUST SPRAY

(Contd. of page 15)

- · Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 5

- · Short title of the exposure scenario Professional use of sprays
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

· Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- Risk management measures
- · Worker protection
- Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.

(Contd. on page 17)

version number 4.0 (replaces version 3.3)

Revision: 21.10.2024

Trade name: ANTIRUST SPRAY

Printing date 21.10.2024

(Contd. of page 16)

- · Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- · Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

Annex: Exposure scenario 6

- · Short title of the exposure scenario Private use of sprays
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- Product category

PC14 Metal surface treatment products

PC34 Textile dyes, and impregnating products

- · Process category PROC11 Non industrial spraying
- · Environmental release category

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

- Description of the activities / processes covered in the Exposure Scenario See section 1 of the annex to the Safety Data Sheet.
- · Conditions of use
- · Duration and frequency 5 workdays/week.
- · Physical parameters
- · Physical state Fluid
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting consumer exposure Not required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures No special measures required.
- · Technical protective measures No special measures required.
- Personal protective measures No special measures required.
- · Measures for consumer protection No special measures required.
- Environmental protection measures
- · Air No special measures required.
- · Water No special measures required.
- · Disposal measures Ensure that waste is collected and contained.
- · Disposal procedures Dispose of product residues with household waste.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer Not relevant for this Exposure Scenario.
- · Guidance for downstream users No further relevant information available.

GB