

# SPRAY WITH PTFE

Dry lubricant

**Description**

SPRAY WITH PTFE is a dry-film lubricant; it can be used as an anti-friction agent and separating agent that does not leave behind any oily marks. With a particle size of 5 µm, the wafer-thin PTFE layer prevents parts from sticking together. Almost absolute chemical resistance and a very broad service temperature range (+265°C). Anti-static.

**Product features**

- dry lubricant
- adhesive
- smoothing
- water-resistant
- temperature-stable

**Notes**

Shake the can well before use until the mixing ball is moving freely.

**Field of application**

SPRAY WITH PTFE is ideal for hygienic dry lubrication. Other application examples include sliding rails and guide rails, conveyor belts, transport rollers and transport chutes, window mechanisms, blind systems and rolling shutter systems, permanent lubrication for shafts in plastic bearings or in the case that other lubricants such as mineral oils or silicone are not desired for the respective application or a further processing stage.

**Application**

Briefly spray the area in question from a distance of 10–20 cm and leave to dry.



## Container

	Item no.	Container sizes	EAN-Code
SPRAY WITH PTFE	302348	Spray 200 Milliliter	7611197164357
	302349	Carton 12 X 200 Milliliter	7611197901839

The above information corresponds to the current state of knowledge. We reserve the right to make changes. The measurement and production tolerances customary in the industry apply to the stated characteristic data. A safety data sheet on the product described is available.