



cod. 1560  
Fianchetti laterali in crosta  
Side panels in waxed suede




I 1




II

III



IV E



V

**I:** Per poter montare i nostri fianchetti, rimuovere la sella e il pannello laterale (1) originali. Conservare viti e pezzi rimossi, alcuni serviranno per il montaggio dei fianchetti.

**II:** I fianchetti sono due: sinistro e destro. Ogni fianchetto ha una tasca sul lato interno.

**III:** Sono forniti anche due pannelli in plastica (E), due clip (B), due viti piccole (C) e due grandi (D).

**IV:** Far passare il fianchetto sotto al telaio e fissarlo con la vite tipo torx (A) e lo spessore in gomma originali interponendo lo spessore tra la superficie del serbatoio e il fianchetto. Posizionare la clip (B) in corrispondenza del foro indicato sul serbatoio. Inserire il pannello (E) nella tasca del fianchetto facendo combaciare i fori.

**IV-V:** Piegare il fianchetto per far combaciare i suoi fori con i rispettivi sul serbatoio poi fissare con la vite piccola (C) e la vite grande (D).

**I:** In order to mount our side panels, remove the original seat and lateral panel (1). Save the screws and the other removed components, some of them will be used later.

**II:** There are two side panels: one left, one right. Each side panel has a pocket on the inside.

**III:** Side panels come also with two plastic panels (E), two clips (B), two smaller screws (C) and two bigger screws (D).

**IV:** Let the side panel go under the frame and fix it with the original torx screw (A) and rubber thickness placing the thickness between the tank and the side panel surfaces. Place the clip (B) in correspondence of the illustrated hole on the tank. Insert the panel (E) in the pocket matching the holes.

**IV-V:** Fold the side panel to match its holes with the corresponding holes on the tank then fix with the smaller screw (C) and the bigger screw (D).

NB: Ripetere per entrambi i lati

NB: Repeat for both sides



cod. 1560  
Fianchetti laterali in crosta  
Side panels in waxed suede




I 1




II

III



IV E



V

**I:** Per poter montare i nostri fianchetti, rimuovere la sella e il pannello laterale (1) originali. Conservare viti e pezzi rimossi, alcuni serviranno per il montaggio dei fianchetti.

**II:** I fianchetti sono due: sinistro e destro. Ogni fianchetto ha una tasca sul lato interno.

**III:** Sono forniti anche due pannelli in plastica (E), due clip (B), due viti piccole (C) e due grandi (D).

**IV:** Far passare il fianchetto sotto al telaio e fissarlo con la vite tipo torx (A) e lo spessore in gomma originali interponendo lo spessore tra la superficie del serbatoio e il fianchetto. Posizionare la clip (B) in corrispondenza del foro indicato sul serbatoio. Inserire il pannello (E) nella tasca del fianchetto facendo combaciare i fori.

**IV-V:** Piegare il fianchetto per far combaciare i suoi fori con i rispettivi sul serbatoio poi fissare con la vite piccola (C) e la vite grande (D).

**I:** In order to mount our side panels, remove the original seat and lateral panel (1). Save the screws and the other removed components, some of them will be used later.

**II:** There are two side panels: one left, one right. Each side panel has a pocket on the inside.

**III:** Side panels come also with two plastic panels (E), two clips (B), two smaller screws (C) and two bigger screws (D).

**IV:** Let the side panel go under the frame and fix it with the original torx screw (A) and rubber thickness placing the thickness between the tank and the side panel surfaces. Place the clip (B) in correspondence of the illustrated hole on the tank. Insert the panel (E) in the pocket matching the holes.

**IV-V:** Fold the side panel to match its holes with the corresponding holes on the tank then fix with the smaller screw (C) and the bigger screw (D).

NB: Ripetere per entrambi i lati

NB: Repeat for both sides